

Safety Data Sheet

x45 Black

Revision date : 2021/04/16

Version: 6.0

Page: 1/11

(30770320/SDS_GEN_US/EN)

1. Identification

Product identifier used on the label

x45 Black

Recommended use of the chemical and restriction on use

Recommended use*: Stereolithography; Monomer in ultraviolet ink jet application; In an enclosed system

* The "Recommended use" identified for this product is provided solely to comply with a Federal requirement and is not part of the seller's published specification. The terms of this Safety Data Sheet (SDS) do not create or infer any warranty, express or implied, including by incorporation into or reference in the seller's sales agreement.

Details of the supplier of the safety data sheet

Company:

Nexa3D
1923 Eastman Ave., STE 200
Ventura, CA 93003, USA

Telephone: +1-805-465-9001

Emergency telephone number

24 Hour Emergency Response Information

ChemTel 1-800-255-3924 (US) / 1-813-248-0585 Contract MIS3892732
BASF HOTLINE: 1-800-832-HELP (4357)

Other means of identification

Chemical family: Preparation based on: urethane, acrylates, Polymer

2. Hazards Identification

According to Regulation 2012 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200

Classification of the product

Acute Tox.	4 (oral)	Acute toxicity
Skin Corr./Irrit.	2	Skin corrosion/irritation
Eye Dam./Irrit.	1	Serious eye damage/eye irritation
Skin Sens.	1B	Skin sensitization
STOT RE	2 (oral)	Specific target organ toxicity — repeated exposure
Aquatic Acute	2	Hazardous to the aquatic environment - acute

Safety Data Sheet

x45 Black

Revision date : 2021/04/16
Version: 6.0

Page: 2/11
(30770320/SDS_GEN_US/EN)

Aquatic Chronic	3	Hazardous to the aquatic environment - chronic
Repr.	2 (fertility)	Reproductive toxicity
Repr.	2 (unborn child)	Reproductive toxicity

Label elements

Pictogram:



Signal Word:
Danger

Hazard Statement:

H318	Causes serious eye damage.
H315	Causes skin irritation.
H302	Harmful if swallowed.
H317	May cause an allergic skin reaction.
H373	May cause damage to organs through prolonged or repeated oral exposure.
H361	Suspected of damaging fertility. Suspected of damaging the unborn child.
H412	Harmful to aquatic life with long lasting effects.
H401	Toxic to aquatic life.

Precautionary Statements (Prevention):

P280	Wear protective gloves, protective clothing and eye protection or face protection.
P260	Do not breathe dust/gas/mist/vapours.
P273	Avoid release to the environment.
P201	Obtain special instructions before use.
P202	Do not handle until all safety precautions have been read and understood.
P272	Contaminated work clothing should not be allowed out of the workplace.
P270	Do not eat, drink or smoke when using this product.
P264	Wash contaminated body parts thoroughly after handling.

Precautionary Statements (Response):

P305 + P351 + P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P310	Immediately call a POISON CENTER or physician.
P308 + P313	IF exposed or concerned: Get medical attention.
P302 + P352	IF ON SKIN: Wash with plenty of soap and water.
P330	Rinse mouth
P362 + P364	Take off contaminated clothing and wash it before reuse.

Precautionary Statements (Storage):

P405	Store locked up.
------	------------------

Precautionary Statements (Disposal):

P501	Dispose of contents/container in accordance with local regulations.
------	---

Hazards not otherwise classified

No specific dangers known, if the regulations/notes for storage and handling are considered.

Safety Data Sheet

x45 Black

Revision date : 2021/04/16
Version: 6.0

Page: 3/11
(30770320/SDS_GEN_US/EN)

3. Composition / Information on Ingredients

According to Regulation 2012 OSHA Hazard Communication Standard; 29 CFR Part 1910.1200

diphenyl(2,4,6-trimethylbenzoyl)phosphine oxide

CAS Number: 75980-60-8

Content (W/W): $\geq 1.0 - < 3.0\%$

Synonym: Diphenyl(2,4,6-trimethylbenzoyl)phosphineoxide

Phenyl acrylate

CAS Number: Trade Secret

Content (W/W): $\geq 1.0 - < 3.0\%$

Synonym: No data available.

2-Propen-1-one, 1-(4-morpholinyl)-

CAS Number: 5117-12-4

Content (W/W): $\geq 50.0 - < 75.0\%$

Synonym: No data available.

Acrylate derivative

CAS Number: Trade Secret

Content (W/W): $\geq 3.0 - < 5.0\%$

Synonym: No data available.

Urethane-acrylate oligomer

CAS Number: Trade Secret

Content (W/W): $\geq 25.0 - < 50.0\%$

Synonym: No data available.

4. First-Aid Measures

Description of first aid measures

General advice:

Immediately remove contaminated clothing.

If inhaled:

If difficulties occur after vapour/aerosol has been inhaled, remove to fresh air and seek medical attention.

If on skin:

Wash affected areas thoroughly with soap and water. Seek medical attention.

If in eyes:

Seek medical attention. Hold eyes open and rinse slowly and gently with water for 15 to 20 minutes. Remove contact lenses, if present, after first 5 minutes, then continue rinsing.

If swallowed:

Immediately rinse mouth and then drink 200 - 300 ml water, do not induce vomiting, seek medical attention. Never induce vomiting or give anything by mouth if the victim is unconscious or having convulsions.

Most important symptoms and effects, both acute and delayed

Safety Data Sheet

x45 Black

Revision date : 2021/04/16
Version: 6.0

Page: 4/11
(30770320/SDS_GEN_US/EN)

Symptoms: Information, i.e. additional information on symptoms and effects may be included in the GHS labeling phrases available in Section 2 and in the Toxicological assessments available in Section 11.

Information on: Phenyl acrylate

Symptoms: Overexposure may cause: Eye irritation, skin irritation, erythema, nausea, headache, vomiting, dizziness, diarrhea, abdominal cramps

Indication of any immediate medical attention and special treatment needed

Note to physician

Treatment:

Treat according to symptoms (decontamination, vital functions), no known specific antidote.

5. Fire-Fighting Measures

Extinguishing media

Suitable extinguishing media:
water spray, dry powder, foam

Unsuitable extinguishing media for safety reasons:
water jet

Special hazards arising from the substance or mixture

Hazards during fire-fighting:
harmful vapours

Evolution of fumes/fog. The substances/groups of substances mentioned can be released in case of fire.

Advice for fire-fighters

Protective equipment for fire-fighting:
Wear a self-contained breathing apparatus.

Further information:

The degree of risk is governed by the burning substance and the fire conditions. Contaminated extinguishing water must be disposed of in accordance with official regulations.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Use personal protective clothing. Keep people away and stay on the upwind side.

Environmental precautions

Do not discharge into drains/surface waters/groundwater.

Methods and material for containment and cleaning up

Spills should be contained, solidified, and placed in suitable containers for disposal.

Safety Data Sheet

x45 Black

Revision date : 2021/04/16
Version: 6.0

Page: 5/11
(30770320/SDS_GEN_US/EN)

7. Handling and Storage

Precautions for safe handling

Keep away from sources of ignition - No smoking.

Protection against fire and explosion:

Heated containers should be cooled to prevent polymerization. Take precautionary measures against static discharges.

Conditions for safe storage, including any incompatibilities

Further information on storage conditions: Protect against heat. Protect from the effects of light. The stabilizer is only effective in the presence of oxygen. Handle and open container with care. Close container tightly after use.

Protect from temperatures below: 0 °C

Protect from temperatures above: 40 °C

8. Exposure Controls/Personal Protection

No occupational exposure limits known.

Advice on system design:

Provide local exhaust ventilation to control vapours/mists.

Personal protective equipment

Respiratory protection:

Wear a NIOSH-certified (or equivalent) organic vapour/particulate respirator. A NIOSH-certified respirator with an APF of at least 50 is required. Observe OSHA regulations for respirator use (29 CFR 1910.134).

Hand protection:

Wear chemically impervious protective gloves., Polyethylene-Laminate (PE laminate) - ca. 0.1 mm coating thickness, chloroprene rubber (Neoprene), nitrile rubber (NBR) - 0.4 mm coating thickness, Manufacturer's directions for use should be observed because of great diversity of types.

Eye protection:

Tightly fitting safety goggles (chemical goggles) and face shield.

Body protection:

Body protection must be chosen depending on activity and possible exposure, e.g. apron, protecting boots, chemical-protection suit (according to EN 14605 in case of splashes or EN ISO 13982 in case of dust).

General safety and hygiene measures:

Handle in accordance with good industrial hygiene and safety practice. Avoid contact with the skin, eyes and clothing. Avoid inhalation. Wearing of closed work clothing is recommended.

9. Physical and Chemical Properties

Form:	liquid
Odour:	acrylic-like
Odour threshold:	No data available.
Colour:	black
pH value:	7

Safety Data Sheet

x45 Black

Revision date : 2021/04/16
Version: 6.0

Page: 6/11
(30770320/SDS_GEN_US/EN)

Freezing point:	not determined	
Melting point:	not determined	
boiling temperature:	> 100 °C (1,013 hPa)	
Flash point:	> 100 °C	
Flammability:		(derived from flash point)
Lower explosion limit:	not determined For liquids not relevant for classification and labelling. The lower explosion point may be 5 - 15 °C below the flash point.	
Upper explosion limit:		(DIN 51649-1)
	not determined For liquids not relevant for classification and labelling.	
Autoignition:	not determined	
Vapour pressure:	not determined	
Density:	1.09 g/cm3 (55 °C) 1.12 g/cm3 (20 °C)	
Relative density:	No data available.	
Vapour density:	not determined	
Partitioning coefficient n-octanol/water (log Pow):	not applicable for mixtures	
Self-ignition temperature:	not self-igniting	
Thermal decomposition:	195 °C, 300 - < 400 kJ/kg	
Viscosity, dynamic:	approx. 300 mPa.s (20 °C) 100 mPa.s (50 °C)	
Solubility in water:	sparingly soluble	
Solubility (qualitative):	soluble	
	solvent(s): organic solvents,	
Evaporation rate:	not determined	

10. Stability and Reactivity

Reactivity

No hazardous reactions if stored and handled as prescribed/indicated.

Oxidizing properties:
not fire-propagating

Chemical stability

The product is stable if stored and handled as prescribed/indicated.

Possibility of hazardous reactions

The product is stabilized against spontaneous polymerization prior to despatch.
The product can polymerize if the shelf life or storage temperature are greatly exceeded. Heat develops during polymerization. Reacts with peroxides and other radical components.

Conditions to avoid

No conditions known that should be avoided.

Safety Data Sheet

x45 Black

Revision date : 2021/04/16
Version: 6.0

Page: 7/11
(30770320/SDS_GEN_US/EN)

Incompatible materials

free radical initiators

Hazardous decomposition products

Decomposition products:

Hazardous decomposition products: No hazardous decomposition products if stored and handled as prescribed/indicated.

Thermal decomposition:

195 °C, 4 K/min

11. Toxicological information

Primary routes of exposure

Routes of entry for solids and liquids are ingestion and inhalation, but may include eye or skin contact. Routes of entry for gases include inhalation and eye contact. Skin contact may be a route of entry for liquefied gases.

Acute Toxicity/Effects

Acute toxicity

Assessment of acute toxicity: Of moderate toxicity after single ingestion.

Virtually nontoxic by inhalation. Virtually nontoxic after a single skin contact. The product has not been tested. The statement has been derived from the properties of the individual components.

Oral

Type of value: ATE

Value: 1,120 mg/kg

Inhalation

Type of value: ATE

Value: > 20 mg/l

Determined for vapor

Type of value: ATE

Value: > 5 mg/l

Determined for mist

Dermal

Type of value: ATE

Value: > 5,000 mg/kg

Assessment other acute effects

Assessment of STOT single:

Based on the available information there is no specific target organ toxicity to be expected after a single exposure.

The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

Irritation / corrosion

Assessment of irritating effects: Skin contact causes irritation. May cause severe damage to the eyes.

Safety Data Sheet

x45 Black

Revision date : 2021/04/16
Version: 6.0

Page: 8/11
(30770320/SDS_GEN_US/EN)

Skin

Species: rabbit

Result: Irritant.

Method: BASF-Test

The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

Eye

Species: rabbit

Result: Irritant.

Method: BASF-Test

The product has not been tested. The statement has been derived from substances/products of a similar structure or composition.

Sensitization

Assessment of sensitization: Sensitization after skin contact possible.

Guinea pig maximization test

Species: guinea pig

Result: sensitizing

Method: OECD Guideline 406

The product has not been tested. The statement has been derived from the properties of the individual components.

Aspiration Hazard

No aspiration hazard expected.

Chronic Toxicity/Effects

Repeated dose toxicity

Assessment of repeated dose toxicity: Repeated oral exposure may affect certain organs.

Genetic toxicity

Assessment of mutagenicity: Based on the ingredients, there is no suspicion of a mutagenic effect.

Carcinogenicity

Assessment of carcinogenicity: The whole of the information assessable provides no indication of a carcinogenic effect.

Reproductive toxicity

Assessment of reproduction toxicity: The results of animal studies suggest a fertility impairing effect. The product has not been tested. The statement has been derived from the properties of the individual components.

Information on: diphenyl(2,4,6,-trimethylbenzoyl)phosphine oxide

Assessment of reproduction toxicity: The results of animal studies suggest a fertility impairing effect.

Teratogenicity

Assessment of teratogenicity: Possible risk of harm to the unborn child. The product has not been tested. The statement has been derived from the properties of the individual components.

Other Information

The product has not been tested. The statement has been derived from the properties of the individual components.

Safety Data Sheet

x45 Black

Revision date : 2021/04/16
Version: 6.0

Page: 9/11
(30770320/SDS_GEN_US/EN)

12. Ecological Information

Toxicity

Toxicity to fish

LC50 (96 h) > 1.27 mg/l, *Leuciscus idus* (OECD 203; ISO 7346; 84/449/EEC, C.1, semistatic)
The product has not been tested. The statement has been derived from the properties of the individual components.

Aquatic invertebrates

No data available.

Aquatic plants

No observed effect concentration (72 h) 10 - 100 mg/l (growth rate), *Scenedesmus subspicatus* (Guideline 92/69/EEC, C.3, static)
The product has not been tested. The statement has been derived from the properties of the individual components.

Chronic toxicity to fish

No data available regarding toxicity to fish.

Chronic toxicity to aquatic invertebrates

No data available regarding toxicity to daphnids.

Microorganisms/Effect on activated sludge

Toxicity to microorganisms

The inhibition of the degradation activity of activated sludge is not anticipated when introduced to biological treatment plants in appropriate low concentrations.

Persistence and degradability

Assessment biodegradation and elimination (H₂O)

Poorly biodegradable.

Bioaccumulative potential

Assessment bioaccumulation potential

The product has not been tested.

Mobility in soil

Assessment transport between environmental compartments

No data available.

Additional information

Add. remarks environm. fate & pathway:

Treatment in biological waste water treatment plants has to be performed according to local and administrative regulations.

Other ecotoxicological advice:

Acutely harmful for aquatic organisms.

Safety Data Sheet

x45 Black

Revision date : 2021/04/16
Version: 6.0

Page: 10/11
(30770320/SDS_GEN_US/EN)

13. Disposal considerations

Waste disposal of substance:

Dispose of in accordance with national, state and local regulations. Do not discharge into drains/surface waters/groundwater.

Container disposal:

Recommend crushing, puncturing or other means to prevent unauthorized use of used containers. Dispose of in accordance with national, state and local regulations.

14. Transport Information

Land transport

USDOT

Not classified as a dangerous good under transport regulations

Sea transport

IMDG

Not classified as a dangerous good under transport regulations

Air transport

IATA/ICAO

Not classified as a dangerous good under transport regulations

15. Regulatory Information

Federal Regulations

Registration status:

Chemical TSCA, US released; restriction on use / listed

TSCA §5. Based on EPA's assessment that includes analogue data, a substance in this product has the potential to cause:

Carcinogenicity;

Genetic toxicity;

Specific target organ toxicity.

Hazard(s) not classifiable under GHS criteria.

This product contains a substance (CASRN 5117-12-4) which may cause internal organ and reproductive effects.

When using this product, use skin protection.

TSCA § 5(a) final Significant New Use Restriction (SNUR)

40 CFR 721.5185

EPCRA 311/312 (Hazard categories): Refer to SDS section 2 for GHS hazard classes applicable for this product.

State regulations

State RTK

PA

CAS Number

1333-86-4

Chemical name

carbon black

Safety Data Sheet

x45 Black

Revision date : 2021/04/16
Version: 6.0

Page: 11/11
(30770320/SDS_GEN_US/EN)

Safe Drinking Water & Toxic Enforcement Act, CA Prop. 65:

WARNING: This product can expose you to chemicals including CARBON BLACK (AIRBORNE, UNBOUND PARTICLES OF RESPIRABLE SIZE [≤ 10 MICROMETERS]), which is known to the State of California to cause cancer, and METHANOL, which is known to the State of California to cause birth defects or other reproductive harm. For more information, go to www.P65Warnings.ca.gov.

NFPA Hazard codes:

Health: 3 Fire: 1 Reactivity: 1 Special:

16. Other Information

SDS Prepared by:

BASF NA Product Regulations
SDS Prepared on: 2021/04/16

We support worldwide Responsible Care® initiatives. We value the health and safety of our employees, customers, suppliers and neighbors, and the protection of the environment. Our commitment to Responsible Care is integral to conducting our business and operating our facilities in a safe and environmentally responsible fashion, supporting our customers and suppliers in ensuring the safe and environmentally sound handling of our products, and minimizing the impact of our operations on society and the environment during production, storage, transport, use and disposal of our products.

Ultracur3D® ST 45 B is a registered trademark of BASF Corporation or BASF SE
IMPORTANT: WHILE THE DESCRIPTIONS, DESIGNS, DATA AND INFORMATION CONTAINED HEREIN ARE PRESENTED IN GOOD FAITH AND BELIEVED TO BE ACCURATE, IT IS PROVIDED FOR YOUR GUIDANCE ONLY. BECAUSE MANY FACTORS MAY AFFECT PROCESSING OR APPLICATION/USE, WE RECOMMEND THAT YOU MAKE TESTS TO DETERMINE THE SUITABILITY OF A PRODUCT FOR YOUR PARTICULAR PURPOSE PRIOR TO USE. NO WARRANTIES OF ANY KIND, EITHER EXPRESSED OR IMPLIED, INCLUDING WARRANTIES OF MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE, ARE MADE REGARDING PRODUCTS DESCRIBED OR DESIGNS, DATA OR INFORMATION SET FORTH, OR THAT THE PRODUCTS, DESIGNS, DATA OR INFORMATION MAY BE USED WITHOUT INFRINGING THE INTELLECTUAL PROPERTY RIGHTS OF OTHERS. IN NO CASE SHALL THE DESCRIPTIONS, INFORMATION, DATA OR DESIGNS PROVIDED BE CONSIDERED A PART OF OUR TERMS AND CONDITIONS OF SALE. FURTHER, YOU EXPRESSLY UNDERSTAND AND AGREE THAT THE DESCRIPTIONS, DESIGNS, DATA, AND INFORMATION FURNISHED BY OUR COMPANY HEREUNDER ARE GIVEN GRATIS AND WE ASSUME NO OBLIGATION OR LIABILITY FOR THE DESCRIPTION, DESIGNS, DATA AND INFORMATION GIVEN OR RESULTS OBTAINED, ALL SUCH BEING GIVEN AND ACCEPTED AT YOUR RISK. Any other intended applications should be discussed with the manufacturer.

END OF DATA SHEET